

U01-1-103

UNIVERSAL CLUTCH CABLE KIT  
93 inch ( 2.35m) IMPERIAL FITTINGS



Part No.	Description	Qty
LB3TS	Conduit 7mm $\varnothing$ with Teflon liner (8mm $\varnothing$ ferrule crimped to 1 end)	93" 2.35m
P19/2	Inner cable 1x19 strand wire 2.0mm $\varnothing$ (6mm $\varnothing$ x10mm nipple cast to 1 end)	103" 2.60m
BN610	Barrel nipple $\varnothing$ 6mm x 10mm	1
F101	Stepped ferrule with $\varnothing$ 6.2mm nose	1
F103	Stepped ferrule with $\varnothing$ 7.0mm nose	1
BN89L	Loose barrel nipple $\varnothing$ 8mm x 9mm	1
TN24	Trumpet nipple $\varnothing$ 3.5mm- $\varnothing$ 5.8mm x 9.5mm	1
A31/137U	Adjuster 5/16 UNF x 1 3/8" (24 TPI)	1
LN31U	5/16 UNF Lock Nut	1
A26B	Adjuster 1/4 BSF x 1 1/2" (26 TPI)	1
LN250B	1/4 BSF Lock Nut	1
M4002	Neoprene rubber boot	1
N8	Nylon nipple sleeve $\varnothing$ 8 mm	1
N10	Nylon nipple sleeve $\varnothing$ 3/8" (10mm)	1

This high quality universal clutch cable kit includes **93 inch (2.35m)** of standard black conduit with Teflon liner, **103 inch (2.60m)** of inner wire and selection of fittings. One end of the inner wire is fitted with a barrel nipple (BN610 6mm $\varnothing$  x 10mm). The other end will need to be cut to length and the required nipple soldered in place. The ferrules and adjusters are a snug fit on the conduit. They can be bonded in place during the assembly or use a centre punch to make a small indentation in their side. The fittings can be adapted for a range of models. Basic soldering kit is needed to solder the nipples in place.

Venhill Engineering Ltd  
21 Ranmore Road  
Dorking  
Surrey  
RH4 1HE