

WORKSHOP CLUTCH AND THROTTLE CABLE KIT

This kit combines the clutch and the throttle kit in handy storage box. Typical application: motorcycle clutch cables, throttle cables and choke cables. Supplied with 10m of conduit, with a black PVC cover, 10m of low friction liner and 10m of inner wire.

A range of nipples and high quality fittings are also included. The ferrules and bends are a snug fit on the conduit. They can be bonded in place during the assembly, or crimped / retained with a small centre punch indentation to their side. The fittings can be adapted for a range of models. There are enough fittings in the kit to make at least ten lines (5 clutch and 5 throttle). Additional fittings, conduit and wire can be purchased separately as required. You will need a basic soldering kit to solder the nipples in place. We recommend our 'bird caging' tool to make the bond with the nipples stronger prior to soldering. Part no. VT13

Kit Contents:

| Part No. | Description | Qty | Part No. | Description | Qty |
|----------|--|-----|------------|--|-----|
| LB1TS | 5mm CONDUIT W/ TEFLON LINER | 10M | A675B | MIDWAY ADJUSTER, THREAD 20mm LONG | 3 |
| LB3TS | 7mm CONDUIT W/ TEFLON LINER | 10M | F1 | FERRULE FOR LB1TS CONDUIT 5.5mm O.D. | 40 |
| R77/1 | 1.5mm O.D. 7 X 7 GALVANISED WIRE ROPE | 10M | F2B | FERRULE FOR LB1TS CONDUIT 6.3mm O.D. | 20 |
| P19/2 | 2mm O.D. 1 X 19 GALVANISED WIRE STRAND | 10M | F100 | FERRULE FOR LB3TS CONDUIT 8mm O.D. | 10 |
| BN575/55 | BARREL NIPPLE 6mm O.D. x 5mm | 10 | F101 | FERRULE FOR LB3TS CONDUIT 6.2mm O.D.NOSE | 10 |
| BN89L | LOOSE BARREL NIPPLE 8mm O.D. X 9mm | 10 | F103 | FERRULE FOR LB3TS CONDUIT 7mm O.D. NOSE | 10 |
| BN610 | BARREL NIPPLE 6mm O.D. x 9.5 mm | 10 | EE7 | CARBURETTOR NIPPLE 3mm O.D. x 3mm | 40 |
| BN1010L | LOOSE BARREL NIPPLE 10mm O.D x 10mm | 10 | TN24 | TRUMPET NIPPLE 3.5mm-5.8mm O.D x 9.5mm | 25 |
| BN1013L | BARREL NIPPLE 9.5mm x 13mm (3/8in O.D. x 1/2in) | 10 | TN17 | TRUMPET NIPPLE 4.4mm-7.9mm O.D.x 12.6mm | 25 |
| BA5 | BALL NIPPLE 5mm O.D. | 25 | TN24A | TRUMPET NIPPLE 3.5mm-6.3mm O.D x 5.1mm | 25 |
| A61B | MIDWAY ADJUSTER. THREAD 32mm LONG | 3 | M5931 | UNIV. NEOPRENE BOOT 7mm I.D. | 20 |
| A8125/42 | STEEL ADJUSTER M8 X 1.25 X 42mm | 3 | M4002 | NEOPRENE ADJ BOOT UNIVERSAL | 10 |
| A8125/25 | ALLOY ADJ SCREW M8 x 1.25 x 25mm | 3 | M6902A | NEOPRENE TAPERED BOOT I/D 10 & 4.5mm | 4 |
| FB10125 | FERRULE BEND HONDA/THROTTLE OPEN BLACK | 1 | FB8 | FERRULE BEND HONDA - THROTTLE CLOSE | 1 |
| FB22W | FERRULE TUBE 45DEG BEND - THROTTLE | 2 | FB13 | FERRULE BEND SUZUKI THROTTLE OPEN BLACK | 1 |
| FB14 | FERRULE BEND - SUZUKI THROTTLE CLOSE | 1 | FB23 | FER. BEND THROTTLE CLOSE M10x1 (TRIUMPH) | 1 |
| FB26 | FERRULE BEND OPEN THROTTLE (TRIUMPH) | 1 | TB3A | WIRE GUIDE - FEMALE TOP OPENING | 1 |
| TB3B | WIRE GUIDE - MALE BOTTOM CLOSE | 1 | M6903 | RUBBER BOOT - PUSH/PULL THROTTLE | 1 |
| LN6100 | M6 X1.00 HALF LOCK NUT | 6 | A6100/32/1 | M6 X 1.00 STEEL ADJUSTER SCREW 32mm LONG | 3 |
| LN8125 | M8 X 1.25 LOCK NUT | 12 | | | |