

U01-4-402
 UNIVERSAL HD THROTTLE CABLE
 KIT. PUSH FIT
 6mm CONDUIT, 1.25m



Description	Qty
Conduit 6mm O.D.	1.25m
Inner cable 1.2mm wire rope with a fixed ball nipple on one end of 4.3mm O.D.	1.65m
Slotted Barrel nipple \varnothing 6mm x 6.5mm	2
Solderless Barrel nipple \varnothing 6mm x 10mm	2
90 degrees push fit ferrule bends	2
75 degrees push fit ferrule bends	2
Neoprene rubber boots	2
Small spring \varnothing 4.5mm x 9mm	1
Ferrule \varnothing 5.5mm nose crimped onto one end of the conduit.	1
Ferrule \varnothing 4.8mm nose crimped onto one end of the conduit.	1
Instant Glue	1



This high-quality universal Harley Davidson throttle cable kit includes **1.25m** of standard black conduit (6mm \varnothing), **1.65m** of inner wire (1.2mm \varnothing) and selection of fittings. One end of the inner wire is fitted with a ball nipple (4.3mm \varnothing). The other end will need to be cut to length and the required nipple tightened in place. The ferrules are crimped on the conduit at one end. The ferrule bends can be bonded in place during the assembly with glue or use a centre punch to make a small indentation in their side. The fittings can be adapted for a range of models.