


U01-1-100
 UNIVERSAL CLUTCH CABLE KIT
 1.35m METRIC FITTINGS



Part No.	Description	Qty
LB3TS	Conduit 7mm \varnothing with Teflon liner (8mm \varnothing ferrule crimped to 1 end)	1.35m
P19/2	Inner cable 1x19 strand wire 2.0mm \varnothing (6mm \varnothing x10mm nipple cast to 1 end)	1.60m
BN610	Barrel nipple \varnothing 6mm x 10mm	1
F101	Stepped ferrule with \varnothing 6.2mm nose	1
F103	Stepped ferrule with \varnothing 7.0mm nose	1
BN89L	Loose barrel nipple \varnothing 8mm x 9mm	1
TN24	Trumpet nipple \varnothing 3.5mm- \varnothing 5.8mm x 9.5mm	1
A8125/42	Steel adjuster screw M8 x 1.25 x 42mm	1
LN8125	Lock nut M8 x 1.25mm	1
M4002	Neoprene rubber boot	1
N8	Nylon nipple sleeve \varnothing 8 mm	1
N10	Nylon nipple sleeve \varnothing 3/8" (10mm)	1

This high quality universal clutch cable kit includes **1.35m** of standard black conduit with Teflon liner, **1.60m** of inner wire and selection of fittings. One end of the inner wire is fitted with a barrel nipple (BN610 6mm \varnothing x 10mm). The other end will need to be cut to length and the required nipple soldered in place. The ferrules and adjusters are a snug fit on the conduit. They can be bonded in place during the assembly or use a centre punch to make a small indentation in their side. The fittings can be adapted for a range of models. Basic soldering kit is needed to solder the nipples in place.